

Pression en "bars" roue de remorques

| En bars | SARIS | EDUARD | HAPERT | HUMBAUR | TWINS | TWIN TECH | WmMEYER |
|-----------------------------|------------------|---------------|---------------|----------------|--------------|------------------|----------------|
| 140/70 R12 | | 2,50 | | | | | |
| 145 R13 | | | | | | | 2,60 |
| 145/70 R13 | | 3,20 | 3,00 | | | | 2,70 |
| 145/80 R10 - R13 | | | | 3,00 | | | |
| 145R12 | 2,20 | | | | | | |
| 155 R13 C | | | | | | | 4,50 |
| 155 R13; RF; R13 C | | | | 3,50 | | | |
| 155/70 R12 C | 6,20 | | 6,50 | 6,25 | | | 6,25 |
| 155/70 R13 | | | | 3,00 | | | 2,70 |
| 155/80 R13 | | 3,10 | 2,90 | 3,00 | | | |
| 155R13 | 2,40 | 3,00 | | | | | 2,50 |
| 165 R13 | | | | | | | 2,70 |
| 165 R13 C | | | 4,50 | | | | 4,50 |
| 165 R13 C8 | 4,50 | 4,50 | | | | | |
| 165/70 R13 | 2,50 | | | | | | |
| 175 R14 | | | 4,50 | | 4,50 | | |
| 175/65 R14 | 2,50 | | | | | | |
| 175/65 R15 | | | | | | | 2,90 |
| 175/65 R15 RF | | | | | | | 2,90 |
| 175/70 R13 | 2,50 | 2,75 | | 3,00 | 2,70 | | 2,70 |
| 175/80 R14 | | | | 3,00 | | | 2,60 |
| 18,5 x 8,5 - 8 | | | 3,40 | 3,50 | | | 3,40 |
| 185 R14 | | | | | | | 2,50 |
| 185 R14 C | | | 4,50 | 4,50 | | 4,50 | |
| 185 R14 C8 | 4,50 | | | | 5,50 | | |
| 185 R14C 6PR | | | | | | | 3,75 |
| 185 R14C 8PR | | | | | | | 3,75 |
| 185/60 R12 | | 6,50 | | | | 6,30 | |
| 185/60 R14 | | | | | | | 2,70 |
| 185/60 R15 | | | | 3,00 | | | |
| 185/65 R14 | | | | 3,00 | | | |
| 185/65 R15 | | | | 3,00 | | | |
| 185/70 R13 | 2,50 | 3,00 | 3,00 | | 2,70 | | |
| 185/70 R13C | | | 6,00 | | | | |
| 185/70 R14 | | | | 3,00 | | | |
| 195 R14 C - 8PR | | | | 4,50 | 4,50 | 4,50 | 4,50 |
| 195 R14 C 6PR | | | | | | | 3,75 |
| 195/50 B10 | | | | | 6,20 | | 6,00 |
| 195/50 R10 C | | | | 6,25 | 6,20 | | |
| 195/50 R13C | 6,50 | 6,50 | 6,50 | 6,25 | | 6,30 | 6,25 |
| 195/50 R15 | | | | | 3,00 | | |
| 195/55 R10 C | | | 6,50 | | | | 6,00 |
| 195/55 R10F | | 6,25 | | | | | |
| 195/55 R13 C | | | | 6,50 | 6,20 | | |
| 195/60 R12 | | | | | | 6,30 | |
| 195/60 R14 | | | | 3,00 | | | |
| 195/65 R14 | | | | 3,00 | | | |
| 195/65 R15 | 2,90 | | | 3,00 | | | 2,70 |
| 195/65 R15 RF | | | | 3,40 | | | 3,10 |
| 195/70 R14 | 2,50 | | | 3,00 | | | 3,00 |
| 195/70 R14 RF | | | | | | | 2,80 |
| 195/70 R15 RF | | | | | | | 3,10 |
| 20.5 x 10.0 - 10 | | | | | | | 6,25 |
| 205/60 R15 | | | | 3,00 | | | |
| 205/65 R15 | | | | 3,00 | | | 2,70 |
| 205/65 R15 RF | | | | 4,50 | | | 3,10 |
| 205/70/R15C | | | 3,80 | | | | |
| 225/55 B12 C | | | | | | | 6,25 |
| 5.00 - 10 C | | | | | | | 3,50 |
| 5.00 x 10 | 2,90 | | | | | | |
| Dimension de Clé | 19 mm | | | | | | |
| Filetage | M12 x 1,5 | | | | | | |
| Couple serrage acier | 80-90Nm | 96 | | 90 | 90 | 90 | |
| Couple serrage Alu | | | | 120 | 120 | | |