

Pression en "bars" roue de remorques

En bars	SARIS	EDUARD	HAPERT	HUMBAUR	TWINS	TWIN TECH	WmMEYER	ANSSEMS HULCO
140/70 R12		2,50						
145 R13							2,60	2,8
145/70 R13		3,20	3,00				2,70	
145/80 R10 - R13				3,00				2,8
145R12	2,20							
155 R13 C							4,50	
155 R13; RF; R13 C				3,50				
155/70 R12 C	6,20		6,50	6,25			6,25	
155/70 R13				3,00			2,70	
155/80 R13		3,10	2,90	3,00				2,8/2,9
155R13	2,40	3,00					2,50	2,8
165 R13							2,70	
165 R13 C			4,50				4,50	
165 R13 C8	4,50	4,50						
165/70 R13	2,50							
175 R14			4,50		4,50			
175/65 R14	2,50							
175/65 R15							2,90	
175/65 R15 RF							2,90	
175/70 R13	2,50	2,75		3,00	2,70		2,70	
175/80 R14				3,00			2,60	
18,5 x 8,5 - 8			3,40	3,50			3,40	
185 R14							2,50	4,5
185 R14 C			4,50	4,50		4,50		
185 R14 C8	4,50				5,50			
185 R14C 6PR							3,75	
185 R14C 8PR							3,75	
185/60 R12		6,50				6,30		6,5
185/60 R14							2,70	
185/60 R15				3,00				
185/65 R14				3,00				
185/65 R15				3,00				
185/70 R13	2,50	3,00	3,00		2,70			3,4
185/70 R13C			6,00					
185/70 R14				3,00				
195 R14 C - 8PR				4,50	4,50	4,50	4,50	
195 R14 C 6PR							3,75	
195/50 R10					6,20		6,00	6,25
195/50 R10 C				6,25	6,20			
195/50 R13								6,5
195/50 R13C	6,50	6,50	6,50	6,25		6,30	6,25	
195/50 R15					3,00			
195/55 R10 C			6,50				6,00	
195/55 R10F		6,25						
195/55 R13 C				6,50	6,20			
195/60 R12						6,30		
195/60 R14				3,00				
195/65 R14				3,00				
195/65 R15	2,90			3,00			2,70	
195/65 R15 RF				3,40			3,10	
195/70 R14	2,50			3,00			3,00	3,4
195/70 R14 RF							2,80	
195/70 R15 RF							3,10	
20.5 x 10.0 - 10							6,25	
205/60 R15				3,00				
205/65 R15				3,00			2,70	
205/65 R15 RF				4,50			3,10	
205/70/R15C			3,80					
225/55 B12 C							6,25	
5.00 - 10 C							3,50	
5.00 x 10	2,90							
Dimension de Clé	19 mm							
Filetage	M12 x 1,5							
Couple serrage acier	80-90Nm	96		90	90	90		90-120
Couple serrage Alu				120	120			